


# BOSCH Climate 3000i

Self-cleaning mode
i-clean mode
Dry mode
Follow me mode
Wind Avoid me mode
WiFi
Gear mode
Eco mode
Silent mode
Anti-corrosion
8°C heating mode
Low ambient cooling mode
Auto restart
On/off timer
Weekly timer

## Efficient

The Climate 3000i is a versatile reversible air conditioning unit that delivers both heating and cooling from a single source. With an ErP rating of A++ for cooling and A+ for heating, it ensures optimal comfort for you with minimal energy consumption.

## Peace and Quiet

Climate 3000i's silent function reduces the sound level of the indoor and outdoor unit to give you and your neighbours a good night's sleep.

## Breathe in Clean Air

The 'i-clean' function eliminates up to 99% of bacteria. Also the double filtration system eliminates odours, harmful gases and volatile organic compounds in the air.

5 YEARS WARRANTY

# BOSCH ChillFest

Cool Combos ❄ Solo Specials

BUY 2 BOSCH CLIMATE 3000i



GET 1 BOSCH CLIMATE 3000i 12BTU FREE

OR

25% OFF

# BOSCH



## TECHNICAL SPECIFICATIONS

| | | | CLIMATE3000I12 | CLIMATE3000I18 | CLIMATE3000I24 |
|---|---|---|---|---|---|
| COOLING CAPACITY (MIN - NOM - MAX) | | kW | 1.3 - 3.5 - 4.3 | 3.4 - 5.3 - 5.9 | 3.4 - 7.0 - 8.2 |
| COOLING CAPACITY (MAX) | | BTU/h | 14700 | 20130 | 28000 |
| HEATING CAPACITY (MIN - NOM - MAX) | | kW | 1.1 - 3.8 - 4.4 | 1.5 - 5.6 - 5.8 | 3.1 - 7.3 - 8.2 |
| HEATING CAPACITY (MAX) | | BTU/h | 14950 | 19960 | 28000 |
| PDESIGNC | | kW | 3.6 | 5.3 | 7 |
| EER/COP | | W/W | 3.19/3.70 | 3.42/3.20 | 2.91/3.43 |
| SEER/SCOP | | – | 7.0/5.5 | 7.0/5.1 | 6.4/5.1 |
| ENERGY CLASS | | | A++/A+++ | A++/A+++ | A++/A+++ |
| AIR FLOW VOLUME (HI/MI/LO) | | $m^3/h$ | 530/400/350 | 800/600/500 | 1090/770/610 |
| POWER SUPPLY | | V/Ph/Hz | 220-240V, 1PH, 50Hz | 220-240V, 1PH, 50Hz | 220-240V, 1PH, 50Hz |
| POWER INPUT | COOLING | W | 1096 | 1550 | 2402 |
| | HEATING | W | 1027 | 1750 | 2130 |
| CURRENT INPUT | COOLING | A | 4.76 | 6.7 | 10.5 |
| | HEATING | A | 4.46 | 7.6 | 9.3 |
| RATED CURRENT | COOLING | A | 10 | 13 | 19 |
| MAX. DISTANCE | LENGTH | m | 25 | 30 | 50 |
| | HEIGHT | m | 10 | 20 | 25 |
| **OUTDOOR UNIT** | | | **CL3000IU 3.5 E** | **CL3000IU 5.3** | **CL3000I 7.0 E** |
| NET DIMENSIONS(W x H x D) | | mm | 720x270x495 | 874x330x554 | 955x342x673 |
| NET/GROSS WEIGHT | | Kg | 23.7/25.5 | 33.5/36.1 | 43.9/46.9 |
| SOUND PRESSURE LEVEL/SOUND POWER LEVEL | | dB(A) | 55/62 | 57/65 | 60/67 |
| ADDITIONAL GAS CHARGE | | g/m | 12 | 12 | 24 |
| REFRIGERANT TYPE | | | R32 | R32 | R32 |
| REFRIGERANT CHARGE | | kg | 0.65 | 1.1 | 1.45 |
| LIQUID PIPE DIAMETER/GAS PIPE DIAMETER | | mm (inch) | Φ6.35mm(1/4in)/Φ9.52mm(3/8in) | Φ6.35(1/4in)/Φ12.7(1/2in) | Φ9.52(3/8in)/Φ15.9(5/8in) |
| MAX. PIPE LENGTH WITHOUT ADDITIONAL CHARGE | | m | 5 | 5 | 5 |
| OPERATION RANGE FOR COOLING/HEATING | | ℃ | -15 ~ 50/-15 ~ 24 | -15 ~ 50/-15 ~ 24 | -15 ~ 50/-15 ~ 24 |
| **INDOOR UNIT** | | | **CL3000IU W 3.5 E** | **CL3000IU W 5.3** | **CL3000IU W 7.0** |
| REFRIGERANT TYPE | | | R32 | R32 | R32 |
| NET DIMENSIONS(W x H x D) | | mm | 802x200x295 | 971x228x321 | 1082x234x337 |
| NET/GROSS WEIGHT | | Kg | 8.7/11.5 | 11.2/14.6 | 13.6/17.3 |
| SOUND PRESSURE LEVEL (HI/MI/LO) | | dB(A) | 37/32/22 | 41/37/31 | 46/37/34.5 |
| SOUND POWER LEVEL | | dB(A) | 56 | 56 | 62 |

*Bosch reserves the right to modify the specifications without prior notice, please confirm the final specifications with sales representatives.


dlgroupmalta.com
sales@dl-group.co
Business Workspace,Triq l-Irħam Marsa Malta.


dl group